

D2

00010000 (247625382 IN)

00020000 (248128512 IN)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
3 January 2003 (20.01.2003)

(11) International Publication Number
WO 03/001776 A1

(51) International Classification
H01L 50/00, G06F 01/16

(12) International Application Number
PCT/US2001/1776

(21) International Filing Date
4 June 2001 (04.06.2001)

(22) Filing Language
English

(23) Publication Language
English

(24) Priority Date
22 June 2001 (22.06.2001) US

(71) Applicant: DOV, GLOBAL TECHNOLOGIES INC.
10101 Whittier Street, 1700 Building, Midland, MI
48674 (US)

(72) Inventors: HUN, Michael E.; 3114 Neale Court, Midland, MI 48640 (US); CLEGG, Michael E.; 3508
Lambert Road, Midland, MI 48642 (US); WATKINS,
John D.; 3200 Whittier Street, Midland, MI 48674
(US); LANCHESTER, Joseph A.; 1724 Oak Oak, Oak, MI
48723 (US); PETERSON, Curtis E.; 3000 Cadillac
Lane, Midland, MI 48642 (US); EDWARDS, Mary,
Mc; 1808 Bonfield Drive, Midland, MI 48642 (US);
FLAHERTY, Patrick A.; 1000 Constance Lane, Midland, MI
48642 (US).


(84) Designated States (epoonly): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CZ,
DE, DK, DM, DZ, EC, EG, ES, FI, FR, GB, GR, GU, HK,
HU, IL, IN, JP, KE, KG, KH, KR, KZ, LA, LT, LU, LV,
MA, MD, ME, MG, MK, MN, MU, MV, MW, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RO,
RU, SA, SD, SE, SG, SI, SK, SL, SM, SN, SR, ST, SV,
SZ, TH, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, YE, ZA, ZM,
ZW.

(85) Designated States (epoonly): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CZ,
DE, DK, DM, DZ, EC, EG, ES, FI, FR, GB, GR, GU, HK,
HU, IL, IN, JP, KE, KG, KH, KR, KZ, LA, LT, LU, LV,
MA, MD, ME, MG, MK, MN, MU, MV, MW, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RO,
RU, SA, SD, SE, SG, SI, SK, SL, SM, SN, SR, ST, SV,
SZ, TH, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, YE, ZA, ZM,
ZW.

(86) Designated States (epoonly): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CZ,
DE, DK, DM, DZ, EC, EG, ES, FI, FR, GB, GR, GU, HK,
HU, IL, IN, JP, KE, KG, KH, KR, KZ, LA, LT, LU, LV,
MA, MD, ME, MG, MK, MN, MU, MV, MW, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RO,
RU, SA, SD, SE, SG, SI, SK, SL, SM, SN, SR, ST, SV,
SZ, TH, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, YE, ZA, ZM,
ZW.

(87) Designated States (epoonly): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CZ,
DE, DK, DM, DZ, EC, EG, ES, FI, FR, GB, GR, GU, HK,
HU, IL, IN, JP, KE, KG, KH, KR, KZ, LA, LT, LU, LV,
MA, MD, ME, MG, MK, MN, MU, MV, MW, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RO,
RU, SA, SD, SE, SG, SI, SK, SL, SM, SN, SR, ST, SV,
SZ, TH, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, YE, ZA, ZM,
ZW.

WO 03/001776 A1



(64) THE PROTECTIVE SEALABLE TRANSPARENT MEMBRANE FOR ELECTRONIC TOUCH SCREENS

(57) Abstract: A protective sealable transparent membrane (1) comprised of a film (11) and a frame (12) which is supported above a touch screen of a personal electronic device (45) secured in a protective enclosure (1). The protective sealable transparent membrane (1) allows activation of the touch screen, avoids incidence and a wear and tear light seal.

WO 03/001776
PCT/US2001/1776
PROTECTIVE SEALABLE TRANSPARENT FLEXIBLE MEMBRANE FOR
ELECTRONIC TOUCH SCREENS

The present invention relates to a protective sealable transparent membrane which covers the touch screen of a personal electronic device enclosed in a protective enclosure.

Personal electronic devices, such as hand held computers, cell phones, pagers, personal digital assistants (PDAs), gaming devices, electronic music players, voice recorders, global positioning systems (GPS) and the like, have become common place in today's society. These personal electronic devices have found utility in all aspects of life including personal and/or professional activities. A touch screen is commonly used to input and view data into personal electronic devices. The advantage of a touch screen is that the operator may simply touch the display object or portion of the screen to highlight or select or otherwise input information.

In most environments, and in outdoor environments in particular, personal electronic devices are subject to liquids, dust, foods, grease, moisture and other contaminants. Contamination of the touch screen can adversely affect the operability of the personal electronic device. Following contamination, these devices need to be cleaned, further exposing the personal electronic devices to harsh cleaning fluids, liquids and solutions. Thus, in order to operate properly in harsh environments, an enclosure with a protective transparent membrane having a liquid tight seal is needed to protect sensitive electronic display elements.

Prior art techniques have attempted to solve this problem in several ways. Typically, an enclosure with a front cover for a touch screen contains one or more gaskets. Not only do gaskets leak with time and exposure to environmental contamination and cleaning fluids, but they also require the use of additional assembly steps and addition of the gasket(s) itself. The gasket must be attached and sealed properly in order to function effectively. The use of gaskets requires multiple operations and parts which makes front covers using gaskets expensive to manufacture. Gaskets also tend to leak after a relatively short period of time due to the expansion and contraction of the gasket itself due to temperature changes in the environment.

Other attempts to solve the problem involve an enclosure with an operable/closable protective lid. These solutions are less than desirable as they are not sealed to liquids and must be opened to activate the touch screen, thus providing opportunities for exposing the touch screen to potential contamination. One such example is taught in US-A-5,990,874 of

a personal electronic device with an attachable openable/closable lid where there is limited capability to activate the touch screen by depressing the protective lid while closed. Unfortunately, the lid does not provide a seal to liquids and the elements and the only function through the lid is the ability to turn the personal electronic device on or off.

Accordingly, a need exists for a protective sealable transparent flexible membrane for personal electronic devices having touch screens encased in a protective enclosure, which allows activation of the touch screen through the membrane, provides an effective liquid and dust tight seal and protects the touch screen from the environment and elements. Further, it is desirable that the number of parts, assembly steps and hence the cost can be reduced.

FIG. 1 is a perspective view showing the protective transparent flexible membrane.

FIG. 2 is a perspective view of the protective transparent flexible membrane and underside of the top portion of the protective enclosure for a personal electronic device that the protective transparent flexible membrane fits into.

FIG. 3 is an exploded perspective view of the protective transparent flexible membrane, top portion of the protective enclosure, a personal electronic device and the mating bottom portion of the protective enclosure.

It is an objective of the invention to provide a protective sealable transparent flexible membrane that fits into a protective enclosure for a personal electronic device through which the touch screen can be viewed.

It is another objective of the invention to provide a protective sealable transparent flexible membrane that when in place in the protective enclosure provides protection and scratch resistance for the touch screen of the personal electronic device.

It is another objective of the invention to provide a protective sealable transparent flexible membrane that when in place in the protective enclosure provides a liquid, especially water, tight seal.

It is another objective of the invention to provide a protective sealable transparent flexible membrane that when in place in the protective enclosure provides a particulate, especially dust, tight seal.

It is yet another objective of the invention to provide a protective sealable transparent flexible membrane that when in place in the protective enclosure allows for activation of the touch screen on the personal electronic device through the membrane.

It is still a further objective of the invention to provide a protective sealable transparent flexible membrane that is easy to replace.

It is still a further objective of the invention to provide a protective sealable transparent flexible membrane that is easy to manufacture.

An embodiment of the present invention is a protective sealable transparent flexible membrane comprising a film and a frame, which fits into a protective enclosure and is suspended above a personal electronic device, said protective sealable transparent flexible membrane provides a liquid and particulate tight seal.

In a further embodiment of the present invention, the film is a flexible transparent thermoplastic, preferably a transparent thermoplastic polyurethane elastomer.

In a further embodiment of the present invention, the frame is a flexible thermoplastic elastomer, preferably a thermoplastic polyurethane elastomer.

In a further embodiment of the present invention, the film and frame are the same or different flexible thermoplastic elastomer, preferably the same or different thermoplastic polyurethane elastomer.

In a further embodiment of the invention the film is a flexible thermoplastic, preferably a thermoplastic urethane elastomer, with a hardness of between Shore 50 A to Shore 65 D.

In yet a further embodiment of the present invention, the protective sealable transparent flexible membrane comprises buttons, preferably molded-in buttons.

In yet a further embodiment of the invention, the protective sealable transparent flexible membrane comprises decorative printing.

The present invention is a protective sealable transparent flexible membrane. Said protective sealable transparent flexible membrane fits into a protective enclosure which houses a personal electronic device having a display and/or touch screen, such as a hand held computer, cell phone, a pager, a personal digital assistant (PDA), a gaming device, an electronic music player, a video recorder, a global positioning system (GPS) and the like. The protective sealable transparent flexible membrane 1 shown in FIG. 1 having a top side and an underside and comprising a film 11 and a frame 12. As shown in FIG. 2, the protective sealable transparent flexible membrane 1 fits into the underside of the top portion of a protective enclosure 21 having an under side 22 and a top side 23. The protective sealable transparent flexible membrane 1 can fit into the top side or underside of the top portion of the protective enclosure 21. The frame 12 forms a mechanical seal with a mating

00050000 (2462-5502-2 (M))

WO 64/001776

PCT/US69/17728

recess 24 in the top portion of the protective enclosure 21. The top portion of the protective enclosure 21 mates with a bottom portion of the protective enclosure 31 as shown in FIG. 3 to form the protective enclosure for a personal electronic device 43.

The film 11 can be made from any transparent or preferably transparent thermoplastic by any known film making process known in the art. Preferably, the film is made from a transparent or transparent polyamide, polyurethane (PU), polycarbonate (PC), polyvinyl chloride (PVC), polyolefin (PO), such as polyethylene (PE) and polypropylene (PP), polyacrylate, polyester, polysiloxane, polystyrene (PS), styrene and acrylonitrile copolymer (SAN) or mixtures thereof. Preferably the film is a thermoplastic polyurethane (TPU). Preferably the film 11 is a thermoplastic elastomer.

The film is must allow for activation of the touch screen through it, for example by depressing the film. Preferably the film is an elastomer. Moreover, the film has good flex fatigue resistance so as to recover its original position after being depressed when activating the touch screen, rigid enough to maintain its position above the touch screen so as to minimize unwanted screen activation, good hardness so as to afford scratch resistance, good solvent resistance and good long term creep properties so that it will not sag over time. Preferred hardness is equal to or greater than Shore 50 A and equal to or less than Shore 65 D.

Preferably the film 11 has a thickness equal to or greater than 0.001 millimeter (mm), preferably equal to or greater than 0.01 mm, more preferably equal to or greater than 0.02 mm and most preferably equal to or greater than 0.04 mm. Preferably the film 11 has a thickness equal to or less than 0.5 mm, preferably equal to or less than 0.1 mm, more preferably equal to or less than 0.08 mm, even more preferably equal to or less than 0.06 mm and most preferably equal to or less than 0.05 mm.

The frame 12 can be made from any thermoplastic elastomer which can (1) be adhered to the film and (2) make a liquid and particulate tight mechanical seal when fitted into the recess 24 in the top portion of the protective enclosure 21. Suitable elastomers are described, for example, in Billmeyer, R., *Textbook of Polymer Science*, Interscience Publishers, New York, N.Y. (1965) and in *Kirk-Othmer Science of Chemical Technology* 4th Ed., John Wiley & Sons, New York, N.Y. (1993). Preferably the frame is made from a thermoplastic elastomer such as thermoplastic polyolefin (TPO), polyethylene, such as low density polyethylene (LDPE), ethylene and vinyl acetate copolymer (EVA), ethylene and propylene copolymer (EP), polyvinyl chloride, polyurethane, polycarbonate, polyester and

00050000 (2462-5502-2 (M))

WO 64/001776

PCT/US69/17728

mixtures thereof. Preferably the frame is made from a thermoplastic polyurethane, such as PELLETHANE™ 2102-75A available from The Dow Chemical Company.

The film 11 and the frame 12 may be made from different thermoplastic elastomers or the same thermoplastic elastomer. Preferably the film 11 and the frame 12 are made from thermoplastic polyurethane.

The protective sealable transparent flexible membrane 1 is a single part, but the film 11 and the frame 12 may be one or more distinct parts. If the film 11 and frame 12 are a single part, it must comprise a transparent or transparent thermoplastic elastomer. If the film 11 and frame 12 are two or more parts, the frame can be made by any known plastic processing technique, such as injection molding, thermforming, extrusion and the cutting, and the like. The film 11 and the frame 12 may be attached to one another by any means known in the art to form the protective sealable transparent flexible membrane, for example by a mechanical bond or physically with adhesives, solvent bonding, heat sealing, sonic welding or insert molding. A preferable method of bonding 11 to 12 is insert molding, for example injection molding or thermforming the frame 12 over the film 11 to form the protective sealable transparent flexible membrane 1.

The protective sealable transparent flexible membrane can vary in size, preferably it enables a view of the personal electronic device within the protective enclosure and more preferably a view of the touch screen of the personal electronic device 43 housed within the protective enclosure.

EXAMPLE

The following example serves to demonstrate an embodiment of the invention but is not intended to limit the scope of the invention.

A thermoplastic polyurethane flexible film available as P79200 U type S-2332, manufactured from Doerfield having a thickness of 0.043 mm and a hardness in the range of Shore 50A to Shore 65 D is used. The frame comprises PELLETHANE 2102-75A from the Dow Chemical Company. The protective sealable transparent flexible membrane is formed by insert injection molding the frame onto the film in an injection molding machine having a mold cavity in the shape of the frame. A piece of the P79200 U type S-2332 film, larger than the frame cavity, is placed between the mold halves, the mold is closed and PELLETHANE 2102-75A is insert molded onto the P79200 U type S-2332 film. The PELLETHANE 2102-75A is dried at a temperature between 80 to 95°C and the molding conditions are a melt temperature between 200 to 215°C with a mold temperature between

00070001 (2462344862 int)

00080000 (2462344862 int)

WFO 63061776

PCT/US2017/728

15 to 60°C. The combined frame and film are removed from the mold and excess film is
 10 die cut away to provide a protective sealable transparent flexible membrane of the desired
 shape.

5 The resulting protective sealable transparent flexible membrane is placed into a top
 portion of a protective enclosure such that the frame mates with a recess in the top portion
 of the protective enclosure to form a water and dust tight seal. A personal electronic device
 is placed in the protective enclosure and the top portion of the protective enclosure is mated
 with the bottom portion of the protective enclosure. The resulting protective sealable
 transparent flexible membrane allows for activation of the touch screen as well as good
 10 scratch resistance, water and dust resistance.

WFO 63061776

PCT/US2017/728

CLAIMS:

1. A protective sealable transparent flexible membrane comprising a film and a
 frame, which fit into a protective enclosure for a personal electronic device wherein said
 membrane is suspended above the personal electronic device allowing activation of the
 5 personal electronic device and provides a liquid and particulate tight seal.

2. The protective sealable transparent flexible membrane of Claim 1 wherein
 the film comprises a transparent thermoplastic elastomer.

3. The protective sealable transparent flexible membrane of Claim 2 wherein
 the film comprises a transparent thermoplastic polyurethane.

4. The protective sealable transparent flexible membrane of Claim 1 wherein
 the frame comprises a thermoplastic elastomer.

5. The protective sealable transparent flexible membrane of Claim 4 wherein
 the frame comprises a thermoplastic polyurethane.

6. The protective sealable transparent flexible membrane of Claim 4 wherein
 the frame has a hardness between Shore 50 A to Shore 65 D.

7. The protective sealable transparent flexible membrane of Claim 1 further
 comprising molded-in buttons.

8. The protective sealable transparent flexible membrane of Claim 1 further
 comprising decorative printing.

00090000 (247965022 87)

00100000 (24614350142 87)

W/O 02/01/76

PCT/US2017/28

W/O 02/01/76

PCT/US2017/28

1/3

2/3

FIG. 1






FIG. 2



313

FIG. 3



INTERNATIONAL SEARCH REPORT		Pub. No. and Application No. PCT/US 02/17728
<p>According to International Patent Classification (IPC) or to both national classification and IPC</p> <p>Int. Cl. 2006 (A61K 31/00) H01K 5/06 G06F 1/16</p> <p>IPC 7 H01K 5/06 H01K 5/06</p>		
<p>Documentation searched other than references communicable to the patent file and documents not included in the table searched</p> <p>Electronic data have been consulted during the International search process of data base and other practical search means used</p> <p>EPO-Internal, WPI Data, P.A.J, 184-108, INSPEC</p>		
<p>C. OCCURRENCES CONCERNING TO BE RELEVANT</p> <p>Category ?</p> <p>Content of document, with indication, where appropriate, of the relevant passages</p>	<p>Referenced in table No.</p>	<p>Pub. No. and Application No. PCT/US 02/17728</p>
<p>Y US 6,132,367 A (ADAIR EDWIN L) 17 October 2000 (2000-10-17) column 6, line 8 - column 13 column 5, line 66 - column 6, line 32; claim 1; figures</p> <p>Y PATENT ABSTRACTS OF JAPAN vol. 017, no. 569 (P-1618) 22 September 1993 (1993-09-22) A JP 05 143231 A (SHARP CORP.), 11 June 1993 (1993-06-11) abstract</p> <p>Y MO 00 51315 A (KINUNEN JUHA; POKKINEN KARI (FI)); LESKELÄ HEIKKI (FI); MODULO O) 31 August 2000 (2000-08-31) page 6, line 19 - line 25; claim 1; figures</p>	<p>1-5</p> <p>1-5</p> <p>1</p>	<p>1-5</p> <p>1-5</p> <p>1</p>
<p>3. Special categories of cited documents:</p> <p>3.1 Prior documents are listed in the continuation of this C.</p>		
<p>3.2</p> <p>3.3</p> <p>3.4</p> <p>3.5</p> <p>3.6</p> <p>3.7</p> <p>3.8</p> <p>3.9</p> <p>3.10</p> <p>3.11</p> <p>3.12</p> <p>3.13</p> <p>3.14</p> <p>3.15</p> <p>3.16</p> <p>3.17</p> <p>3.18</p> <p>3.19</p> <p>3.20</p> <p>3.21</p> <p>3.22</p> <p>3.23</p> <p>3.24</p> <p>3.25</p> <p>3.26</p> <p>3.27</p> <p>3.28</p> <p>3.29</p> <p>3.30</p> <p>3.31</p> <p>3.32</p> <p>3.33</p> <p>3.34</p> <p>3.35</p> <p>3.36</p> <p>3.37</p> <p>3.38</p> <p>3.39</p> <p>3.40</p> <p>3.41</p> <p>3.42</p> <p>3.43</p> <p>3.44</p> <p>3.45</p> <p>3.46</p> <p>3.47</p> <p>3.48</p> <p>3.49</p> <p>3.50</p> <p>3.51</p> <p>3.52</p> <p>3.53</p> <p>3.54</p> <p>3.55</p> <p>3.56</p> <p>3.57</p> <p>3.58</p> <p>3.59</p> <p>3.60</p> <p>3.61</p> <p>3.62</p> <p>3.63</p> <p>3.64</p> <p>3.65</p> <p>3.66</p> <p>3.67</p> <p>3.68</p> <p>3.69</p> <p>3.70</p> <p>3.71</p> <p>3.72</p> <p>3.73</p> <p>3.74</p> <p>3.75</p> <p>3.76</p> <p>3.77</p> <p>3.78</p> <p>3.79</p> <p>3.80</p> <p>3.81</p> <p>3.82</p> <p>3.83</p> <p>3.84</p> <p>3.85</p> <p>3.86</p> <p>3.87</p> <p>3.88</p> <p>3.89</p> <p>3.90</p> <p>3.91</p> <p>3.92</p> <p>3.93</p> <p>3.94</p> <p>3.95</p> <p>3.96</p> <p>3.97</p> <p>3.98</p> <p>3.99</p> <p>3.100</p>	<p>3.1</p> <p>3.2</p> <p>3.3</p> <p>3.4</p> <p>3.5</p> <p>3.6</p> <p>3.7</p> <p>3.8</p> <p>3.9</p> <p>3.10</p> <p>3.11</p> <p>3.12</p> <p>3.13</p> <p>3.14</p> <p>3.15</p> <p>3.16</p> <p>3.17</p> <p>3.18</p> <p>3.19</p> <p>3.20</p> <p>3.21</p> <p>3.22</p> <p>3.23</p> <p>3.24</p> <p>3.25</p> <p>3.26</p> <p>3.27</p> <p>3.28</p> <p>3.29</p> <p>3.30</p> <p>3.31</p> <p>3.32</p> <p>3.33</p> <p>3.34</p> <p>3.35</p> <p>3.36</p> <p>3.37</p> <p>3.38</p> <p>3.39</p> <p>3.40</p> <p>3.41</p> <p>3.42</p> <p>3.43</p> <p>3.44</p> <p>3.45</p> <p>3.46</p> <p>3.47</p> <p>3.48</p> <p>3.49</p> <p>3.50</p> <p>3.51</p> <p>3.52</p> <p>3.53</p> <p>3.54</p> <p>3.55</p> <p>3.56</p> <p>3.57</p> <p>3.58</p> <p>3.59</p> <p>3.60</p> <p>3.61</p> <p>3.62</p> <p>3.63</p> <p>3.64</p> <p>3.65</p> <p>3.66</p> <p>3.67</p> <p>3.68</p> <p>3.69</p> <p>3.70</p> <p>3.71</p> <p>3.72</p> <p>3.73</p> <p>3.74</p> <p>3.75</p> <p>3.76</p> <p>3.77</p> <p>3.78</p> <p>3.79</p> <p>3.80</p> <p>3.81</p> <p>3.82</p> <p>3.83</p> <p>3.84</p> <p>3.85</p> <p>3.86</p> <p>3.87</p> <p>3.88</p> <p>3.89</p> <p>3.90</p> <p>3.91</p> <p>3.92</p> <p>3.93</p> <p>3.94</p> <p>3.95</p> <p>3.96</p> <p>3.97</p> <p>3.98</p> <p>3.99</p> <p>3.100</p>	<p>3.1</p> <p>3.2</p> <p>3.3</p> <p>3.4</p> <p>3.5</p> <p>3.6</p> <p>3.7</p> <p>3.8</p> <p>3.9</p> <p>3.10</p> <p>3.11</p> <p>3.12</p> <p>3.13</p> <p>3.14</p> <p>3.15</p> <p>3.16</p> <p>3.17</p> <p>3.18</p> <p>3.19</p> <p>3.20</p> <p>3.21</p> <p>3.22</p> <p>3.23</p> <p>3.24</p> <p>3.25</p> <p>3.26</p> <p>3.27</p> <p>3.28</p> <p>3.29</p> <p>3.30</p> <p>3.31</p> <p>3.32</p> <p>3.33</p> <p>3.34</p> <p>3.35</p> <p>3.36</p> <p>3.37</p> <p>3.38</p> <p>3.39</p> <p>3.40</p> <p>3.41</p> <p>3.42</p> <p>3.43</p> <p>3.44</p> <p>3.45</p> <p>3.46</p> <p>3.47</p> <p>3.48</p> <p>3.49</p> <p>3.50</p> <p>3.51</p> <p>3.52</p> <p>3.53</p> <p>3.54</p> <p>3.55</p> <p>3.56</p> <p>3.57</p> <p>3.58</p> <p>3.59</p> <p>3.60</p> <p>3.61</p> <p>3.62</p> <p>3.63</p> <p>3.64</p> <p>3.65</p> <p>3.66</p> <p>3.67</p> <p>3.68</p> <p>3.69</p> <p>3.70</p> <p>3.71</p> <p>3.72</p> <p>3.73</p> <p>3.74</p> <p>3.75</p> <p>3.76</p> <p>3.77</p> <p>3.78</p> <p>3.79</p> <p>3.80</p> <p>3.81</p> <p>3.82</p> <p>3.83</p> <p>3.84</p> <p>3.85</p> <p>3.86</p> <p>3.87</p> <p>3.88</p> <p>3.89</p> <p>3.90</p> <p>3.91</p> <p>3.92</p> <p>3.93</p> <p>3.94</p> <p>3.95</p> <p>3.96</p> <p>3.97</p> <p>3.98</p> <p>3.99</p> <p>3.100</p>

00130000 (2477450542 UN)

INTERNATIONAL SEARCH REPORT

Number and Application No.
PCT/US 02/17728

Classification			Document(s) Considered to be Relevant	Number and Application No.
Category	Number of documents, with indication, where appropriate, of the relevant passages			
A	DE 199 25 051 A (ACERMAN ALBERT GRIH CO) 7 December 2000 (2000-12-07) column 4, line 49 - line 59; claims 1-3; figure 2			1, 8
A	68 2 162 355 A (HURET A FILS) 29 January 1986 (1986-01-29) page 1, right-hand column, line 86 - line 99; claims; figures			1, 7

00140000 (2463348642 UN)

INTERNATIONAL SEARCH REPORT

Number and Application No.
PCT/US 02/17728

Class	Classifications	Document(s) Considered to be Relevant	Number and Application No.
Category 1	Number of documents, with indication, where appropriate, of the relevant passages		
US 6132367	A	17-10-2000	US 5812188 A 22-09-1998 US 5957831 A 28-09-1999 US 5802107 A1 22-01-1998 US 5873814 A 23-02-1999
JP 05143233	A	11-06-1993	MONTE
NO 0051315	A	31-08-2000	FI 4231 U1 30-11-1999 AU 5425039 A 14-09-2000 NO 0051315 A1 31-09-2000
DE 19925051	A	07-12-2000	DE 19925051 A1 07-12-2000 DE 0072344 A1 30-11-2000 EP 1181702 A1 27-02-2002
GB 2162355	A	29-01-1986	DE 3422273 A1 19-12-1985 FR 2565157 A1 20-12-1985 IT 1183894 B 22-10-1987

Best Available Copy